## APPROVAL OF PROPOSED INSTALLATION PIPE AND/OR UTILITY LINES

TO:	DATE:
	missioners Court offers no objections to the location on the right-of-way of your proposedas shown by accompanying drawings and notice dated, except
easement in or upon this county improve, relocate, widen, increase moved under the direction of the	e Camp County Commissioners Court does not purport, hereby, to grant and right, claim, title, or road; and it is further understood that in the future should for any reason Camp County need to work, se add to or any manner change the structure of this right-of-way line, this line, if affected, will be Commissioner of the Precinct in which the work is being performed and shall be relocated at the Camp County shall be notified a minimum of 48 hours prior to the beginning of any work.
which the work is being perform	way shall be performed in accordance with the instructions of the Commissioner of the Precinct in ed. The installation shall not damage any part of the highway and adequate provisions must be made e to traffic and adjacent property owners. Special specifications for placing this line are as follows:
1. All ground lines are to be inst	alled a minimum of 36 inches below the flowline of the adjacent drainage or bar ditch.
	ht-of-way and not under surfacing shall be backfilled by tamping in 6-inch horizontal layers. All d from the right-of-way and the excavation finished flush with surrounding natural ground.
3. Lines crossing under surfaced shall extend from crown line to c	roads and under surfaced cross roads within the right-of-way shall be placed by boring. Boring crown line.
line. Pipe used for casing may b and shall be capable of supporting	pressure shall be enclosed in satisfactory casing extending from right-of-way line to right-of-way e of any type approved by the Commissioner of the Precinct in which the work is being performed g the load of roadbed and traffic and shall be so constructed that there will be no leakage of any entire length. Inside diameter of casing shall be at least 2 inches greater than the largest outside couplings.
under or within 50 feet of either	hall be located to cross roadbed at approximately right angles thereto. No lines are to be installed end of a bridge unless approved by the Commissioner of the Precinct in which the work is being shall be placed inside any culvert or within 10 feet of the closest point of same.
	as near the right-of-way lines as is possible and no parallel line will be installed in the roadbed or oadbed unless approved by the Commissioner of the Precinct in which the work is being performed in
7. Overhead lines will have a mi	inimum clearance of 18 feet above the road surface at point of crossing.
times, as well as all operating eq	nall be performed in such a manner that all excavated material be kept off the pavements at all uipment and materials. Do not use equipment or installation procedures which will damage any road any repairs to road surfaces, roadbed, structures or other right-of-way features as direct result of this owner of this line.
	thts and flagmen, when necessary, shall be provided by the contractor or owner. One half of the be open to traffic at all times. All traffic control shall be in accordance with the requirements of MUTCD.
10. Utility company shall install	adequate erosion control measures for any excavation work being performed.
APPROVED:Commissioner Precinct	APPROVED:
Commissioner Precinct	# Chairperson, Camp County Commissioners Court

Adopted 2-8-23